

Dräger Alcotest® 7510 Evidential Alcohol Measuring Device

This compact and robust handheld breath alcohol measuring device is especially designed for advanced screening applications. Ideal for use by police, commerce and industry as an alcohol screening device. The Alcotest® 7510 can in many countries and markets be used as an evidential device.

Large, illuminated display

- Clear and distinct display of text messages – even in difficult lighting situations like direct sunlight or darkness
- Individually adjustable: additional color coding with LEDs to support the information displayed

IR module

- Infrared interface for easy data transfer to Dräger mobile printer or PC. The fixture on the charging cradle can be permanently attached with a PC via USB cable: the USB cable does not need to be removed

Sophisticated charging and storage receptacle

- Maximum flexibility in attaching and charging the device – on the wall, in vehicles or on tables

ST-15093-2008



Mouthpiece ejector

- Quick and easy removal of the standard mouthpieces after testing
- The operator does not come in contact with the mouthpieces

Quick and easy operation

- Measuring and navigation is easy with the proven three button operation

Robust, splash-proof housing

- Ergonomically shaped – suitable for right and left handers
- Non-slip rubberized surface

Benefits

Ergonomic design

The Dräger Alcotest 7510 is a compact and robust handheld instrument which, thanks to its special ergonomic design, is suitable for right or left handed users. A non-slip rubber housing offers optimal grip.

State-of-the-art technology

The Alcotest 7510 uses the latest DrägerSensor technology and benefits from an improved sampling method. Depending on the device configuration, it can also detect residual mouth alcohol. A built-in heating element prevents condensation and ensures quick and accurate measurements even at low temperatures. The device is tamperproof and not sensitive to other substances.

Easy to operate

The device has a simple, three button operation. The user controls all measurements via a single push button. A quick and easy menu navigation is possible with two up and down keys. The device incorporates a transfective, high resolution, monochrome graphic display. The backlit display provides clear text messages ensuring legibility in bright sunlight as well as total darkness. Many languages are available. Three light emitting diodes (LEDs) in red, yellow and green support the information shown on the display.

Hygienic and safe

The device complies with high hygiene requirements. The position of the disposable mouthpiece and the molded hand grip automatically provide a safe, hygienic distance between the operator's hand and the subject. The mouthpieces have a special spacer to avoid contact of the subject's lips with the instrument. Designed for maximum hygiene, a special mouthpiece ejection system initiates quick and simple mouthpiece ejection.

Comprehensive data management The Alcotest 7510 is characterized by a comprehensive data management and a wide range of configuration options. The device captures and stores a wealth of information. Using pick lists or free text, the unit can be customised to suit specific needs. The test result is saved with a test number with corresponding date and time.

Low energy consumption

The device is powered by alkaline or rechargeable NiMH batteries. It can also be supplied with Li-Ion batteries.

High flexibility

The Dräger Alcotest 7510 can be used immediately in any environment. Tests can be carried out at temperatures from -10 °C to +50 °C. The flexible data management, the high memory capacity as well as the option of wireless data transfer to the Dräger Mobile Printer or a computer, allow for easy adjustment

Benefits

to national and international specifications. Via the ambient pressure sensor, the device automatically compensates for the ambient barometric conditions when performing dry-gas tests. The GPS module recognizes the exact geographical location where a breath test is performed. More optional accessories like a stable packaging case and various mounting and charging options are offered.

Accessories

ST-178-2004



Mouthpieces (slide'n'click)

Mouthpieces in packs of 100, 250 and 1,000, with or without non-return valve

ST-14738-2008



12-V charging cable

Car charger

Accessories

ST-14736-2008



Power supply

Power pack (current source)

ST-11932-2008



Charging cradle

Consisting of base, insert to receive the measuring instrument and wall mount

D-12916-2009



PC-Connection cable with Mini-USB

USB cable for data transfer

ST-11924-2008



IR module + holster

Consisting of holster and IR module

Accessories

ST-11898-2008



Holster Set

Consisting of holster, belt loop, and transparent covering flap

D-60003-2012



System case

With space to accommodate the Dräger Alcotest® 7510 instrument, the Dräger Mobile Printer, mouthpieces, batteries, paper rolls, charging cable, USB-Cable, keyboard etc.

ST-8404-2006



Dräger Mobile Printer

The Dräger Mobile Printer prints breath alcohol and drug test measurement results directly on the spot.

Related Products

D-74696-2013



Dräger Alcotest® 6820

Keeping the roads safe and free of impaired drivers is an unpredictable and high stress job. Dräger designed the Alcotest® 6820 handheld breathalyser specifically for the needs of law enforcement officers. It's easy to use and provides fast, reliable results in the toughest environments you face when every second matters.

D-43786-2015



Dräger Alcotest® 9510

The Dräger Alcotest® 9510 is an advanced breath alcohol measuring instrument for evidential applications. It is designed to comply with national and international requirements and regulations (OIML R 126). With dual sensor technology, intuitive color touch screen interface, and modern design the Alcotest® 9510 sets superior standards.

D-54720-2012



Dräger DrugTest® 5000

No pipetting, no drips, no timing: Collecting an oral fluid sample is quick and easy with the Dräger DrugTest® 5000. The collected sample can then be analysed immediately for accurate results on the spot.

Technical Data

Dräger Alcotest® 7510

Principle of measurement	Electrochemical DrägerSensor in 1/4" technology; alcohol-specific
Measurement range	0 to 3.0 mg/L (if the limits of the measuring range are exceeded, a message is displayed).
Sampling	Standard Sampling: Automatic when the minimum volume is reached. Passive Sampling: Without mouthpiece or manual initiation of sampling is possible. The device can detect residual mouth alcohol during the delivery of the breath sample (if this option is activated).
Ready for use	After approx. 6 s after powering up (temperature-dependent)
Display of measurement result	After approx. 6 s (at 0 mg/L); after approx. 12 s (at 0.5 mg/L, room temperature) -10 to +50 °C (14 to 122 °F)
Operating temperature (temperature range is monitored)	
Display	LCD display with background illumination (128 x 160 pixels); 35 mm x 45 mm (1.38" x 1.77")
LED	3 light emitting diodes (LEDs) in red, yellow and green to support display and warning messages
Audible signal	Different signal tones to support display messages and warnings
Datalogger	Storage of > 5,000 tests with test numbers, date and time
Power supply	Four AA alkaline or NiMH batteries, charge status is displayed. Approx. 1,500 breath tests can be performed with one set of batteries. Optional: Lithium-Ion batteries can perform approx. 50% more measurements than with NiMH rechargeable batteries.
Calibration	Wet gas or dry gas calibration. Optional: with absolute pressure sensor for the compensation of atmospheric pressure during dry gas calibration
Dimensions (H x W x D)	Approx. 183 mm x 87 mm x 44 mm / 7.2" x 3.4" x 1.7" with use of alkaline or NiMH batteries; Approx. 183 mm x 87 mm x 49 mm / 7.2" x 3.4" x 1.9" with use of Lithium-Ion batteries Approx. 430 g (0.96 lbs)
Weight (including four NiMH batteries)	
Instrument configuration	Direct menu-guided configuration of instrument settings (PIN required). Additional configuration via PC software
Vibration and shock	Conforms to EN 60068-2-6, EN 60068-2-29
CE Conformity	EMC Directive Low-voltage Directive RoHS-Directive
Data interfaces	IR (via IR Module) and USB for connection to a PC; IR connection to the Dräger Mobile Printer for documentation and data entry (when a keyboard is attached to the Dräger Mobile Printer)

Ordering Information

Dräger Alcotest® 7510	Order-No.
Dräger Alcotest® 7510	83 19 760
Consisting of: measuring device 7510 (mouthpiece positioning from the right), case, 3 mouthpieces, USB-cable and Product-CD	
Dräger Alcotest® 7510, modular system	83 19 700
Configured to customer's requirements and is available with a selection of modules (e.g. GPS, Li-ion batteries and absolute pressure sensor)	
Accessories	
Mouthpieces "Standard" (slide'n'click)	
(100 pieces) each individually packed	68 10 690
Mouthpieces "Standard" (slide'n'click) with non-return valve	
(100 pieces), each individually packed	68 11 055
Power Supply Unit (constant current)	
charging NiMH batteries (18 900 92) inside of the Dräger Alcotest® 7510	83 16 991
Car charger 600 mA	
charging NiMH batteries (18 900 92) inside of the Dräger Alcotest® 7510 using a direct connection to the 12 V DC supply of a motor vehicle.	83 20 252
Dräger Alcotest® 7510 Holster Set	
Consisting of: holster, belt clip, protective cover with hook-and-loop fastener (e.g. to attach inside vehicles).	83 19 761
The device can still be used while in the holster.	
Dräger Alcotest® 7510 Desktop Charging Cradle	
Consisting of: charging cradle base unit, charging cradle adapter and wall bracket. To charge the Dräger Alcotest® 7510 with power supply unit (83 16 991) and car charger 600 mA (83 20 252).	83 19 762
Dräger Alcotest® 7510 IR-Module	
Infrared Interface Adapter for use with the Dräger Alcotest® 7510 Holster Set to enable data transfer. The adapter is connected to a PC using a USB-cable, thus minimising the need to frequently connect and disconnect the cable from the instrument.	83 19 763
Dräger Alcotest® 7510 IR-Module and Holster Set	
Consisting of: Dräger Alcotest® 7510 Holster and IR-Module (83 19 763).	83 19 764
Use in conjunction with 83 19 765 for mobile use.	
Use in conjunction with 83 19 762 for stationary use.	
Dräger Alcotest® 7510 Holster Mobile Upgrade	
Consisting of: belt clip, protective cover and hook-and-loop fastener	83 19 765
Can be seen as an upgrade to the Dräger Alcotest® 7510 IR-Module (83 19 764) or as a spare part kit to the Dräger Alcotest® 7510 Holster Set (83 19 761)	
Dräger Alcotest® 7510 System Case	
With space to accommodate the Dräger Alcotest® 7510 instrument, the Dräger Mobile Printer, mouthpieces, batteries, paper rolls, charging cable, USB-Cable, keyboard etc.	83 23 890
Dräger Mobile Printer	
Printer paper (5 rolls), 7 year shelf life	83 19 310
Printer paper (5 rolls), 25 year shelf life	83 19 002
	83 18 461

Ordering Information

"Compact" Keyboard (QWERTY), English, for PS/2	83 15 497
"Compact" Keyboard (QWERTZ), German, for PS/2	83 15 095
"Compact" Keyboard (AZERTY), French, for PS/2	83 15 142
PC communication cable with Mini-USB for use with the Dräger Mobile Printer	83 18 657

Notes



Not all products, features, or services are for sale in all countries. Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

REGION DACH

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION EUROPE

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Singapore Pte. Ltd.
25 International Business Park
#04-20/21 German Centre
Singapore 609916
Tel +65 6308 9400
Fax +65 6308 9401
asia.pacific@draeger.com

REGION CENTRAL AND SOUTH AMERICA

Dräger Panama S. de R.L.
Complejo Business Park,
V tower, 10th floor
Panama City
Tel +507 377-9100
Fax +507 377-9130
contactcsa@draeger.com

Locate your Regional Sales
Representative at:
www.draeger.com/contact

